

MAPEFLOOR WAX REMOVER

Multi-action de-waxing detergent specifically for the metal-filled double cross-linked wax **Mapelux**



DESCRIPTION

Mapefloor Wax Remover is a multi-action de-waxing detergent for the basic cleaning and removal of all types of metal-filled waxes for cementitious or resin floorings.

TECHNICAL CHARACTERISTICS

- specifically developed for the removal of metal-filled waxes, especially those double cross-linked, like **Mapelux Lucida** and **Mapelux Opaca**;
- it attacks all the components in the wax film, and quickly emulsifies residual materials and dirt;
- it contains a minimum of 90% of primary bio-degradable surfactant components and complete aerobic biodegradation, which conforms to Reg. (CE) N° 648/2004.

ADVANTAGES

- easy to use;
- excellent preparation of surfaces before receiving a new protective wax treatment, for example **Mapelux Lucida** or **Mapelux Opaca**;
- low-foaming.

WHERE TO USE

De-waxing treatment, for instance of the film of **Mapelux Lucida** or **Mapelux Opaca**, to be carried out before a new waxing treatment on resin floors made with the **Mapefloor System** and/or cementitious floors made with the **Ultratop System**, even when mixed with natural aggregates, in civil, residential and tertiary environments. It may also be used for the basic cleaning and de-waxing of linoleum and/or rubber floors (in the case of old floors with this type of material, test beforehand to check for colour-fastness).

HOW TO USE

For normal metal-filled waxes, use **Mapefloor Wax Remover** diluted 5-10% in water (0.5-1 l of product in 10 l of water). For double cross-linked metal-filled waxes, such as **Mapelux Lucida** and **Mapelux Opaca**, use at a concentration of 15% (1.5 l in 10 l of water).

Use floor cleaning machines with a brown abrasive disc installed. Once the washing operation is finished, vacuum the residues and rinse thoroughly.

PACKAGING

10 kg cans.

STORAGE

12 months in its original sealed packaging at a temperature between +10°C and +30°C.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Instructions for the safe use of our products can be found on the latest version of the Safety Data Sheet, available from our website www.mapei.com.

PRODUCT FOR PROFESSIONAL USE

TECHNICAL DATA (typical values)

PRODUCT IDENTITY

Appearance:	liquid
Colour:	pink
Density:	1.023 g/cm ³
Content of active substances:	38%
pH of concentrated product:	12.3±0.3
Solubility in water:	soluble
Solubility in oil:	insoluble

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

Mapei S.p.A.

Via Cafiero, 22, 20158, Milano



+39-02-376731



www.mapei.com



mapei@mapei.it

2067-6-2025 en (IT)

Any reproduction of texts, photos and illustrations published here is prohibited and subject to prosecution

